

## ZWMD012012

Application: Eyebrow pencil, Camera, Health care product, Auto watering device, and etc.

Standard Metal Geared Motor

Output Power: 0.01W~1.2W

Metal output shaft

Model	Application Parameters								Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm					
	Rated	At No Load		At Rated Load			Voltage VDC	Speed rpm						Current mA	Speed rpm	Current mA	Torque	
						gf.cm											mN.m	
ZWMD012012-4	3.0	2381	70	1525	255	9	0.9	32.4	300	1000	4	12.4						
ZWMD012012-6	3.0	1587	70	1017	255	14	1.3		300	1000	6							
ZWMD012012-16	3.0	584	75	381	255	31	3.0	36.2	1000	3000	16	16.2						
ZWMD012012-24	3.0	389	75	254	255	46	4.5		1000	3000	24							
ZWMD012012-36	3.0	260	75	169	255	69	6.8		1000	3000	36							
ZWMD012012-64	3.0	145	75	95	260	92	9.0	40.0	1500	4500	64	20.0						
ZWMD012012-96	3.0	96	75	64	260	156	15.3		1500	4500	96							
ZWMD012012-144	3.0	64	75	42	260	234	23.0		1500	4500	144							
ZWMD012012-216	3.0	43	75	28	260	351	34.4		1500	4500	216							
ZWMD012012-256	3.0	36	80	24	260	354	34.7	43.8	2000	5000	256	23.8						
ZWMD012012-384	3.0	24	80	16	260	531	52.0		2000	5000	384							
ZWMD012012-576	3.0	16	80	11	260	796	78.1		2000	5000	576							
ZWMD012012-864	3.0	11	80	7	260	1194	117.1		2000	5000	864							
ZWMD012012-1296	3.0	7	80	5	260	1791	175.6		2000	5000	1296							

\* Above specifications are subject to change without notice, just for reference and customizable according to requirements

