

ZWMD016016

Application: Automechanism transmission, Ad rotaion transmission, ATM , and etc.

Standard Plastic Geared Motor

Output Power: 0.1W~1.5W

Metal output shaft

Model	Application Parameters							Overall Length	Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWMD016016-4	6.0	1961	125	1500	335	29	2.8	37	1500	10000	4	10.1
ZWMD016016-6	6.0	1307	125	1000	335	43	4.2		1000	10000	6	
ZWMD016016-16	6.0	490	135	375	335	92	9.0	40.3	2500	10000	16	13.4
ZWMD016016-24	6.0	327	135	250	335	138	13.6		2500	10000	24	
ZWMD016016-36	6.0	218	135	167	335	207	20.3		2000	10000	36	
ZWMD016016-64	6.0	123	145	94	335	243	23.8	43.6	3500	10000	64	16.7
ZWMD016016-96	6.0	82	145	63	335	365	35.7		3500	10000	96	
ZWMD016016-144	6.0	54	145	42	335	547	53.6		3500	10000	144	
ZWMD016016-216	6.0	36	145	28	335	820	80.4		3000	10000	216	
ZWMD016016-256	6.0	31	145	23	340	729	71.5	46.9	5000	10000	256	20
ZWMD016016-384	6.0	20	145	16	340	1094	107		5000	10000	384	
ZWMD016016-576	6.0	14	145	10	340	1640	161		5000	10000	576	
ZWMD016016-864	6.0	9	145	7	340	2460	241		5000	10000	864	
ZWMD016016-1296	6.0	6	145	5	340	3500	343		3500	10000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

