

## ZWBPD016016

Application: Automechanism transmission, Ad rotaion transmission, ATM , and etc.

Standard Plastic Geared Motor

Output Power: 0.1W~1.5W

Metal output shaft

Model	Application Parameters								Overall Length	Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length
	Rated	At No Load		At Rated Load									
	Voltage	Speed	Current	Speed	Current	Torque							
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m	mm					
ZWBPD016016-4	5.0	1373	85	1125	130	16	1.6	38.4	3000	6000	4	11.5	
ZWBPD016016-6	5.0	915	85	750	130	24	2.4		2000	6000	6		
ZWBPD016016-16	5.0	343	90	281	130	51	5.0	41.7	3000	6000	16	14.8	
ZWBPD016016-24	5.0	229	90	188	130	77	7.5		3000	6000	24		
ZWBPD016016-36	5.0	153	90	125	130	115	11.3		2000	6000	36		
ZWBPD016016-64	5.0	86	95	70	140	135	13.2	45	3000	6000	64	18.1	
ZWBPD016016-96	5.0	53	95	47	140	203	19.9		3000	6000	96		
ZWBPD016016-144	5.0	38	95	31	140	304	29.8		3000	6000	144		
ZWBPD016016-216	5.0	25	95	21	140	456	44.7		2000	6000	216		
ZWBPD016016-256	5.0	21	100	18	150	405	39.7	48.3	3000	6000	256	21.4	
ZWBPD016016-384	5.0	14	100	12	150	608	60		3000	6000	384		
ZWBPD016016-576	5.0	9	100	8	150	911	89		3000	6000	576		
ZWBPD016016-864	5.0	6	110	5	150	1367	134		3000	6000	864		
ZWBPD016016-1296	5.0	4	110	3	150	2000	196		2000	6000	1296		

\* above specifications are subject to change without notice, just for reference and customizable according to requirements

