

ZWBMD020020

Application: Automechanism transmission, Ad rotaion transmission, ATM , and etc.

Standard Plastic Geared Motor

Output Power: 0.5W-1.0W

Metal output shaft

Model	Application Parameters								Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length
	Rated	At No Load		At Rated Load			Overall Length					
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm		mN.m				
ZWBMD020020-4	12.0	1636	70	1420	125	36	3.6	42.7	19000	57000	4	17.6
ZWBMD020020-16	12.0	409	80	355	125	117	11.4	48.0	19000	57000	16	22.9
ZWBMD020020-24	12.0	273	80	237	125	175	17.2		19000	57000	24	
ZWBMD020020-64	12.0	102	90	89	125	308	30.2		19000	57000	64	
ZWBMD020020-96	12.0	68	90	59	125	462	45.3	53.3	19000	57000	96	28.2
ZWBMD020020-144	12.0	45	90	39	125	693	67.9		19000	57000	144	
ZWBMD020020-256	12.0	24	90	22	130	923	90.6	58.6	19000	57000	256	33.5
ZWBMD020020-384	12.0	16	90	15	130	1385	136		19000	57000	384	
ZWBMD020020-576	12.0	11	90	10	130	2078	204		19000	57000	576	
ZWBMD020020-864	12.0	7	90	7	130	3116	306		19000	57000	864	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

