

ZWBPD022022

Application: Optical device, Advertising rotating drive, Bank machines, and etc.

Standard Plastic Geared Motor

Output Power: 0.5W~4.5W

Metal output shaft

Model	Application Parameters							Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWBPD022022-4	24.0	1886	100	1675	295	160	15.7	57.5	10000	30000	4	19.1
ZWBPD022022-6	24.0	1258	100	1117	295	240	23.5		10000	30000	6	
ZWBPD022022-16	24.0	472	110	419	295	512	50.2	64.8	10000	30000	16	26.4
ZWBPD022022-24	24.0	314	110	279	295	768	75.3		10000	30000	24	
ZWBPD022022-36	24.0	210	110	186	295	1152	113.0		10000	30000	36	
ZWBPD022022-64	24.0	118	120	105	295	1350	132.4	72.1	10000	30000	64	33.7
ZWBPD022022-96	24.0	79	120	70	295	2025	198.6		10000	30000	96	
ZWBPD022022-144	24.0	52	120	47	295	3038	297.9		10000	30000	144	
ZWBPD022022-216	24.0	35	120	31	295	4556	446.8		10000	30000	216	
ZWBPD022022-256	24.0	28	120	26	300	4050	397.2	79.4	10000	30000	256	41
ZWBPD022022-384	24.0	19	120	17	300	6075	595.8		10000	30000	384	
ZWBPD022022-576	24.0	13	120	12	300	9113	893.7		10000	30000	576	
ZWBPD022022-864	24.0	8	120	8	300	10000	980.7		10000	30000	864	
ZWBPD022022-1296	24.0	6	120	5	300	4500	441.3		10000	30000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

