

## ZWBMD028028

Application: Optical device, Advertising rotating drive, Bank machines, and etc.

Standard Plastic Geared Motor

Output Power: 0.5W~4.5W

Metal output shaft

Model	Application Parameters							Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWBMD028028-4	24.0	1925	160	1658	400	261	25.6	58.8	40000	120000	4	21.3
ZWBMD028028-6	24.0	1283	160	1105	400	392	38.5		33000	100000	6	
ZWBMD028028-16	24.0	472	150	413	400	837	82.0	67.3	40000	120000	16	29.8
ZWBMD028028-24	24.0	312	150	276	400	1255	123.1		40000	120000	24	
ZWBMD028028-36	24.0	211	150	181	400	1882	184.6	75.8	33000	100000	36	38.3
ZWBMD028028-64	24.0	119	150	104	350	2206	216.3		40000	120000	64	
ZWBMD028028-96	24.0	79	150	69	350	3308	324.5	84.3	40000	120000	96	46.8
ZWBMD028028-144	24.0	54	150	46	350	4963	486.7		40000	120000	144	
ZWBMD028028-216	24.0	35	150	31	350	7444	730.0	84.3	33000	100000	216	46.8
ZWBMD028028-256	24.0	30	150	26	350	6617	648.9		40000	120000	256	
ZWBMD028028-384	24.0	19	150	17	350	9925	973.4	84.3	40000	120000	384	46.8
ZWBMD028028-576	24.0	13	150	12	350	14888	1460.1		40000	120000	576	
ZWBMD028028-864	24.0	9	150	8	350	22332	2190.1	84.3	40000	120000	864	46.8
ZWBMD028028-1296	24.0	6	150	5	350	33000	3236.3		33000	100000	1296	

\* above specifications are subject to change without notice, just for reference and customizable according to requirements

