

ZWBPD028028

Application: Optical device, Advertising rotating drive, Bank machines, and etc.

Standard Plastic Geared Motor

Output Power: 0.5W~4.5W

Metal output shaft

Model	Application Parameters							Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWBPD028028-4	24.0	1925	160	1658	400	261	25.6	58.1	15000	60000	4	20.6
ZWBPD028028-6	24.0	1283	160	1105	400	392	38.5		15000	60000	6	
ZWBPD028028-16	24.0	472	150	413	400	837	82.0		15000	60000	16	
ZWBPD028028-24	24.0	312	150	276	400	1255	123.1	66.6	15000	60000	24	29.1
ZWBPD028028-36	24.0	211	150	181	400	1882	184.6		15000	60000	36	
ZWBPD028028-64	24.0	119	150	104	350	2206	216.3	75.1	15000	60000	64	37.6
ZWBPD028028-96	24.0	79	150	69	350	3308	324.5		15000	60000	96	
ZWBPD028028-144	24.0	54	150	46	350	4963	486.7		15000	60000	144	
ZWBPD028028-216	24.0	35	150	31	350	7444	730.0		15000	60000	216	
ZWBPD028028-256	24.0	30	150	26	350	6617	648.9	83.6	15000	60000	256	46.1
ZWBPD028028-384	24.0	19	150	17	350	9925	973.4		15000	60000	384	
ZWBPD028028-576	24.0	13	150	12	350	14888	1460.1		15000	60000	576	
ZWBPD028028-864	24.0	9	150	8	350	15000	1471.1		15000	60000	864	
ZWBPD028028-1296	24.0	6	150	5	350	15000	1471.1		15000	60000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

