

ZWBMD006006

Standard Plastic Geared Motor

Output Power: 0.01W~0.2W

Metal output shaft

Model	Application Parameters								Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length
	Rated	At No Load		At Rated Load				Overall Length				
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWBMD006006-5	3.0	3824	30	3229	100	3.3	0.32	23.7	330	800	4.8	9.7
ZWBMD006006-6	3.0	2855	30	2411	100	4.4	0.43	23.7	330	800	6.43	9.7
ZWBMD006006-23	3.0	797	34	673	100	13.3	1.31	26.1	330	800	23.04	12.1
ZWBMD006006-31	3.0	595	34	502	100	17.8	1.75	26.1	330	800	30.86	12.1
ZWBMD006006-41	3.0	444	34	375	100	23.9	2.34	26.1	330	800	41.33	12.1
ZWBMD006006-110	3.0	166	37	140	100	54.3	5.33	28.5	330	800	110.6	14.5
ZWBMD006006-148	3.0	124	37	105	100	72.8	7.14	28.5	330	800	148.1	14.5
ZWBMD006006-198	3.0	93	37	78	100	97.5	9.56	28.5	330	800	198.4	14.5
ZWBMD006006-266	3.0	69	37	58	100	130.5	12.80	28.5	330	800	265.7	14.5
ZWBMD006006-531	3.0	35	40	29	100	221.7	21.74	30.9	330	800	530.8	16.9
ZWBMD006006-711	3.0	26	40	21	100	296.9	29.12	30.9	330	800	711.0	16.9
ZWBMD006006-952	3.0	19	40	16	95	330	32.36	30.9	330	800	952.2	16.9
ZWBMD006006-1275	3.0	14	40	12	85	330	32.36	30.9	330	800	1275.2	16.9
ZWBMD006006-1708	3.0	11	40	10	75	330	32.36	30.9	330	800	1707.9	16.9

* above specifications are subject to change without notice, just for reference and customizable according to requirements

