

## ZWBPD006006

Standard Plastic Geared Motor

Output Power: 0.01W~0.2W

Metal output shaft

Model	Application Parameters							Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm	mN.m					
ZWBPD006006-5	3.0	3824	30	3229	100	3.3	0.32	23.7	250	600	4.8	9.7
ZWBPD006006-6	3.0	2855	30	2411	100	4.4	0.43		250	600	6.43	
ZWBPD006006-23	3.0	797	34	673	100	13.3	1.31	26.1	250	600	23.04	12.1
ZWBPD006006-31	3.0	595	34	502	100	17.8	1.75		250	600	30.86	
ZWBPD006006-41	3.0	444	34	375	100	23.9	2.34		250	600	41.33	
ZWBPD006006-110	3.0	166	37	140	100	54.3	5.33	28.5	250	600	110.6	14.5
ZWBPD006006-148	3.0	124	37	105	100	72.8	7.14		250	600	148.1	
ZWBPD006006-198	3.0	93	37	78	100	97.5	9.56		250	600	198.4	
ZWBPD006006-266	3.0	69	37	58	100	130.5	12.80		250	600	265.7	
ZWBPD006006-531	3.0	35	40	29	100	221.7	21.74	30.9	250	600	530.8	16.9
ZWBPD006006-711	3.0	26	40	21	95	250	24.52		250	600	711.0	
ZWBPD006006-952	3.0	19	40	16	90	250	24.52		250	600	952.2	
ZWBPD006006-1275	3.0	14	40	12	80	250	24.52		250	600	1275.2	
ZWBPD006006-1708	3.0	11	40	10	70	250	24.52		250	600	1707.9	

\* above specifications are subject to change without notice, just for reference and customizable according to requirements

