

ZWMD008008

Application: Eyebrow pencil, Camera, Health care product, Robot , and etc.

Standard Metal Geared Motor

Output Power: 0.01W~0.3W

Metal output shaft

Model	Application Parameters								Overall Length	Rated Torque of Gear Box	Instant Torque of Gear Box	Gear Ratio	Gear Box Length		
	Rated	At No Load		At Rated Load			mm	gf.cm						gf.cm	mm
	Voltage	Speed	Current	Speed	Current	Torque									
	VDC	rpm	mA	rpm	mA	gf.cm									
ZWMD008008-4	4.2	4630	90	3361	155	4	0.4	26.1	250	500	3.6	11.6			
ZWMD008008-5	4.2	3125	90	2269	155	6	0.6		250	500	5.3				
ZWMD008008-13	4.2	1228	95	934	155	13	1.2	28.8	400	800	13.0	14.3			
ZWMD008008-19	4.2	829	95	630	155	19	1.8		400	800	19.2				
ZWMD008008-28	4.2	559	95	425	155	27	2.7		400	800	28.4				
ZWMD008008-47	4.2	335	95	259	160	40	3.9	31.5	600	1200	46.7	17.0			
ZWMD008008-69	4.2	226	95	175	160	56	5.5		600	1200	69.1				
ZWMD008008-102	4.2	153	95	118	160	87	8.6		600	1200	102.4				
ZWMD008008-152	4.2	103	95	80	160	123	12.1		600	1200	151.7				
ZWMD008008-168	4.2	91	100	72	160	124	12.2	34.2	750	1500	168.0	19.7			
ZWMD008008-249	4.2	62	100	49	160	176	17.3		750	1500	248.8				
ZWMD008008-369	4.2	42	100	33	160	273	26.8		750	1500	368.6				
ZWMD008008-546	4.2	28	100	22	160	405	39.7		750	1500	546.1				
ZWMD008008-809	4.2	19	100	15	160	599	58.8		750	1500	809.1				

* Above specifications are subject to change without notice, just for reference and customizable according to requirements *

